Material Safety Data Sheet

COMAN

GENUINE DTG WHITE INK PRETREATMENT SOLUTION

Version 2.1

Revision Date 08/13/2014

Ref. 130000129460

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name MSDS Number	:	GENUINE DTG PIGMENT PRETREATMENT SOLUTION 130000129460
Manufacturer/Distributor	:	Colman & Company, Inc. 5409 S Westshore Blvd Tampa FL 33611
Product Information Medical Emergency Transport Emergency	:	1-800-891-1094 1-800-441-3637 (outside the U.S. 1-302-774-1139) CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Potential Health Effects Skin	: May cause skin irritation.
Eyes	: May cause eye irritation.

Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component		CAS-No.	Concentration
Ethylene vinyl acetate copolymer			<10 %
		•	
	1/8		

Material Safety I	Data Sheet
-------------------	------------

colman

GENUINE DTG WHITE INK PRETREATMENT SOLUTION

Version 2.1

			-40.0/
Inorganic salt			<10 %
Non regulated ingredients			>80%
TION 4. FIRST AID MEASUR	ΞS		
Skin contact	: Wash off immediately with plenty before re-use. Get medical attent		
Eye contact	: Immediately flush eye(s) with ple	nty of water. Seek mee	dical advice.
Inhalation	: If inhaled, remove to fresh air. If l breathing, give artificial respiration		
Ingestion	: Is not considered a potential rout vomiting. Call a physician or pois	e of exposure. If swalle on control centre imme	owed Do NOT induce ediately.
TION 5. FIREFIGHTING MEA	SURES		
Flammable Properties Flash point	: > 93.3 °C (> 199.9 °F) Method : closed cup		
Fire and Explosion Hazard	: Not a fire or explosion hazard. Co water spray.	ool closed containers e	exposed to fire with
Suitable extinguishing media	: Not combustible.		
	Use extinguishing measures that the surrounding environment.	are appropriate to loca	al circumstances and
	Keep containers and surrounding	is cool with water spra	у.
	2/8		

colman

GENUINE DTG WHITE INK PRETREATMENT SOLUTION

Version 2.1

Revision Date 08/13/2014	Ref. 130000129460
Firefighting Instructions	 Immediately evacuate personnel to safe areas. Wear suitable protective equipment. Wear self-contained breathing apparatus for firefighting if necessary. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Cool containers/tanks with water spray.
SECTION 6. ACCIDENTAL RELEA	SE MEASURES
	MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. ROTECTIVE EQUIPMENT during clean-up.
Safeguards (Personnel)	: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Wear suitable protective equipment.
Spill Cleanup	: Contain spill. Soak up with inert absorbent material. Collect and contain contaminated absorbent and dike material for disposal. Keep in suitable, closed containers for disposal. Ventilate the area. Clean contaminated surface thoroughly.
Accidental Release Measures	 Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Clean contaminated floors and objects thoroughly while observing environmental regulations. Dispose of in accordance with local regulations.

SECTION 7. HANDLING AND STORAGE

Handling (Personnel)	 Avoid breathing vapours or mist. Do not use in areas without adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Contaminated work clothing should not be allowed out of the workplace. Remove contaminated clothing and protective equipment before entering eating areas. Remove and wash contaminated clothing before re-use.
Handling (Physical Aspects)	: Avoid formation of aerosol.
Storage	: Store at room temperature in the original container. Do not store or consume food, drink or tobacco in areas where they may become contaminated with this material. Keep container closed when not in use. Do not reuse empty container.
	3/8

Material Safety Data Sheet	
GENUINE DTG WHITE IN	IK PRETREATMENT SOLUTION
Version 2.1	
Revision Date 08/13/2014	Ref. 130000129460
	Stable under normal conditions.
SECTION 8. EXPOSURE CONTRO	LS/PERSONAL PROTECTION
Engineering controls	: Local exhaust or a laboratory hood should be used when handling the materials. Maintain air concentrations below occupational exposure standards.
Personal protective equipment Respiratory protection	: Provide adequate ventilation. No personal respiratory protective equipment normally required. Where there is potential for airborne exposures in excess of applicable limits, wear approved respiratory protection with dust/mist cartridge. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.
Hand protection	: Material: Impervious gloves Additional protection: Gloves must be inspected prior to use., Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough., The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other., The exact break through time can be obtained from the protective glove producer and this has to be observed., Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Eye protection	: Wear safety glasses with side shields.
Skin and body protection	 Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Lightweight protective clothing Safety shoes
Exposure Guidelines Exposure Limit Values	
Inorganic salt AEL *	7 mg/m3 8 & 12 hr. TWA
	4/8

Material Safety Data Sheet & company GENUINE DTG WHITE INK PRETREATMENT SOLUTION Version 2.1 Revision Date 08/13/2014 Ref. 130000129460 * AEL is Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence. **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES** Form : liquid Color : clear Odor : odourless pН : 5.9 Boiling point : no data available Specific gravity : ca. 1 Water solubility : miscible SECTION 10. STABILITY AND REACTIVITY Stability : Stable at normal temperatures and storage conditions. Conditions to avoid : None reasonably foreseeable. : None reasonably foreseeable. Incompatibility Hazardous decomposition : Decomposition does not occur under normal use conditions. products Hazardous reactions : Polymerization will not occur. SECTION 11. TOXICOLOGICAL INFORMATION Ethylene vinyl acetate copolymer Skin irritation No skin irritation, Rabbit : Eye irritation : No eye irritation, Rabbit Repeated dose toxicity Oral - feed : Rat Liver effects 5/8

Material Safety Data Sheet

colman

GENUINE DTG WHITE INK PRETREATMENT SOLUTION

Version 2.1

Revision Date 08/13/2014

Ref. 130000129460

- Further information : The substance is a polymer and is not expected to produce toxic effects. Inorganic salt Dermal LD50 > 5,000 mg/kg , Rabbit : Oral LD50 2,301 mg/kg , Rat : Skin irritation No skin irritation, Rabbit : Eye irritation Eye irritation, Rabbit : Mutagenicity : Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Evidence suggests this substance does not cause genetic damage in animals. Teratogenicity : Animal testing showed no developmental toxicity.
- **SECTION 12. ECOLOGICAL INFORMATION** Aquatic Toxicity Ethylene vinyl acetate copolymer The substance is a polymer and is not expected to produce toxic : effects. Inorganic salt 96 h LC50 Fish (unspecified species) 4,630 mg/l : 72 h ErC50 Pseudokirchneriella subcapitata (green algae) 27,000 mg/l OECD : Test Guideline 201 48 h EC50 Daphnia magna (Water flea) 2,400 mg/l OECD Test Guideline 202 : 21 d : EC50 Daphnia magna (Water flea) 610 mg/l **Environmental Fate** Inorganic salt Biodegradability Biodegradable Not applicable 6/8

Material Safety Data She	eet	
GENUINE DTG WHITE	INK PRETREATMENT SOLUTION	0 0 11 1 001 1
Version 2.1		
Revision Date 08/13/2014	Ref. 130000129460	
Bioaccumulation	: Does not bioaccumulate.	
SECTION 13. DISPOSAL CONS	SIDERATIONS	
Waste Disposal	: If recycling is not practicable, dispose of in com Never place unused product down any indoor of	
Container Disposal	 Do not reuse empty container. Contaminated/not cleaned containers should b waste. Dispose of container properly. Refer to applicable Local, State/Provincial, and as industry Standards. 	
SECTION 14. TRANSPORT INF	FORMATION	
SECTION 15. REGULATORY IN	NFORMATION	
TSCA	: On the inventory, or in compliance with the inve	entory
SARA 313 Regulated Chemical(s)	: This material does not contain any chemical con numbers that exceed the threshold (De Minimis by SARA Title III, Section 313.	
California Prop. 65	: WARNING! This product contains a chemical c of California to cause cancer.1,4-Dioxane , Ace Formaldehyde WARNING! This product contains a chemical k California to cause birth defects or other reprod oxide	etaldehyde , Ethylene oxide , known to the State of
	7 / 8	

Material Safety Data Sheet

colman

GENUINE DTG WHITE INK PRETREATMENT SOLUTION

Version 2.1

Revision Date 08/13/2014

Ref. 130000129460

PA Right to Know	: Substances on the Pennsylvania Hazardous Substances List present at
Regulated Chemical(s)	a concentration of 1% or more (0.01% for Special Hazardous
	Substances): 1,4-Dioxane, Ethylene oxide, Formaldehyde

SECTION 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.