

1. Identification	
Product Name Code No. General Use	 ColDesi UV DTF CLEANER and FLUSH UV-Cleaner-500 UV Ink Cleaner/Flush for DTF Printing System
Product Description	: UV Inkjet Cleaning Solution
Supplier Company Address	: COLDESI / COLMAN & COMPANY, INC. : 12198 44th Street North, Clearwater, FL 33762 - USA
Telephone No.	: (800) 891-1094
IN EMERGENCY	Call CHEMTREC, in US and Canada, 800-424-9300 Outside of US or Canada, call 703-527-3887

2. Hazards Identification

Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irritation 2	H315
Eye Irritation 2	H319
Skin Sensitivity 1	H317
Aquatic Chronic 2	H411

Full text of H-phrases: see Section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xi; R36/38 R43 N; R51/53 Full text of R-phrases: see Section 16

Adverse physiochemical, human health and environmental effects No additional information available

Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]



Hazard pictograms (CLP): Signal word (CLP) Hazardous ingredients Hazard statements (CLP)

Warning Hexamethylene diacrylate H315 - Causes skin irritation H317 - May cause an allergic skin reaction H319 - Causes serious eye irritation H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP)

P261 - Avoid breathing vapours, gas, mist, dust

Precautionary Statements

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P260 Do not breathe dust/fume/gas/mist/vapous/spray

P280 - Wear protective gloves, protective clothing, eye protection

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P303+: IF on SKIN (or Hair)

P301+ IF SWALLOWED

P310 Immediately call a POISON CENTER or doctor/physician

P353 Rinse skin with water/shower.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P313 Get medical advice/attention

[Disposal]

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).

Other hazards

No additional information available

No	Chemical Name	Wt%	CAS No.
1	Diethylene glycol butyl ether acetate	60 - 90	124-17-4
2	Diethylene glycol methyl diethyl ether	5 - 20	1002-67-1

3. Composition / Information on Ingredients

3	Tri (N-nitroso-N-phenyl hydroxylamine) aluminum salt	0.1 - 3	15305-07-4

4. First Aid Measures

Inhalation Eye Contact	Remove person to fresh air. If you feel unwell, get medical attention.Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.
Skin Contact	: Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.
Ingestion	Rinse mouth. If you feel unwell, get medical attention.
Most Important	: See Section 11.1. Information on toxicological effects.
Symptoms/Effects	
Indication of Immediate Medical Attention and	: Not applicable.
Special Treatment	
Needed, If Needed	

5. Fire Fighting Measures

Flammable Properties Extinguishing Media	 Flash point >200 ° F Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.
Special Hazards Arising from the Chemical	: Closed containers exposed to heat from fire may build pressure and explode.

Carbon monoxide, Carbon dioxide (During Combustion)
: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.
sures
: Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.
: Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water
 build dikes to prevent entry into sewer systems or bodies of water Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible.

7. Handling and Storage

Precautions for Safe Handling

	: Avoid skin contact with hot material. For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required. Vapors may travel long distances along the ground or floor to an ignition source and flash back.
Conditions for Safe Storage, including any Incompatibilities	: Keep cool. Protect from sunlight. Store away from heat. Store away from oxidizing agents.

8. Exposure Controls / Personal Protection

Control parameters

TABLE BLANK BY DESIGN	

8.2 Exposure controls

9

Appropriate engineering measures : Local exhaust is needed at source of vapours. Keep away from children.

Personal Protective measures : Gloves, Safety glasses, Protective clothing, Wear respiratory mask.

Hand : Nitrile rubber gloves (0,4 mm). Breakthrough time (EN 374-3:2003): > 48 (www.echa.europa.eu)

Eye protection : Chemical goggles or safety glasses (acc. EN 166).

Skin and body protection : Wear suitable protective clothing.

Physical and Chemical Properties

Respiratory protection : Wear approved mask. Do not inhale vapour.

Other protection : Do not eat, drink or smoke when using product.

9. Filysical and Chemical Froperties		
Appearance - Physical State Odor pH level	: Liquid : Acrylate Odor : Not available	
Boiling Point / Boiling Range	:>200 °F	
Melting Point / Melting Range	: Not available	
Decomposition Temperature	: Not available	
Flash Point	:>200 °F	
Auto ignition temperature	: Not available	
Flammability (Solid, Gas)	: Not Applicable	
Explosive Properties	: Not available	
Oxidizing Properties	: Not available	
Upper / Lower Flammability or	: Not available	
Explosive Limits		
Vapor Pressure	∶<10 mmHg [@ 20 ºC]	
Specific Gravity	: 1.04 [Ref Std: WATER=1]	
Solubility	: Not available	6 of 1

Water Solubility	: Negligible
Partition Coefficient (n-octanol / Water)	: Not available
Viscosity	: 4.5-6.5cps(25°C)
Vapor Density	:>1 [Ref Std: AIR=1]
Evaporation Rate	: Not available
VOC	: Not available

10. Stability and Reactivity

Reactivity	: This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.
Chemical Stability	: Stable under normal conditions of use.
Possibility of Hazardous	
Reactions	exposure to heat)
Conditions to Avoid	: Heat
Incompatible Materials	: Strong oxidizing agents
Hazardous	: None known.
Decomposition	

Refer to section 5.2 for hazardous decomposition products during combustion

11. Toxicological Information	
Inhalation	: Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.
Skin Contact	 Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. Allergic Skin Reaction (non-photo induced) in sensitive people:
	Signs/symptoms may include redness, swelling, blistering, and itching.
Eye Contact	: Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision
Ingestion	: May be harmful if swallowed. Gastrointestinal Irritation: 7 of 11

Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Reproductive/Developmental : Contains a chemical or chemicals which can cause birth defects or Toxicity: other reproductive harm.

12. Ecological Information

	Handling is noted because it might influence the environment when
	leaking and abandoning it.
	Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.
Ecotoxicity	: Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.
Persistence and Degradability	: Not available
Bioaccumulation	: Not available
Mobility	: Not available
Other Toxicity	: Not available

13. Disposal Considerations

Regional legislation (waste) Waste disposal recommendations	Disposal must be done according to official regulations. Dispose of this material and its container at hazardous or special waste collection point. Dispose in a safe manner in accordance with local/national regulations. Avoid release to the environment.
Ecology - waste materials European List of Waste (LoW code	Avoid release to the environment.) 08 03 12* - waste ink containing dangerous substances

14. Transport Information

UN Number	Check a thing without a leak in a container. Perform prevention of collapse of cargo surely. :/
Shipping Name	: Environmentally hazardous substance, liquid, n.o.s. (Contains: TETRAHYDROFURFURYL ACRYLATE)
Hazardous Class or Division	:/
Packing Group (PG)	:/
Marine Pollutant	: Yes
Remarks	: Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is excepted from Dangerous Goods regulations. Refer to ICAO/IATA A197, IMDG 2.10.2.7, ADR SP 375.

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

No REACH Annex XVII restrictions Contains no substance on the REACH candidate list VOC content : 0 g/l

National regulations No additional information available

Chemical safety assessment

No chemical safety assessment has been carried out

16. Other Information

Indication of changes: according to Regulation (EC) No. 453/2010.

453/2010.					
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Added			
Data sources : REGULATION (EC) N					
			d packaging of substances and		
Regulation (EC) No		ves 67/548/EEC and 1	999/45/EC, and amending		
Full text of R-, H- and EUH-phrases:	1907/2000.				
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4				
Aquatic Chronic 2	Hazardous to				
		Hazardous to the aquatic environment — Chronic Hazard, Category 2			
Eye Dam. 1 Eye Irrit. 2		Serious eye damage/eye irritation, Category 1 Serious eye damage/eye irritation, Category 2			
	2				
Skin Irrit. 2		Skin corrosion/irrit			
Skin Sens. 1		Sensitisation — S			
Skin Sens. 1A		Sensitisation — Skin, category 1A			
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract				
	irritation				
H302	Harmful if swallowed				
H315	Causes skin irritation				
H317	May cause an allergic skin reaction				
H318	Causes serious eye damage				
H319	Causes serious eye irritation				
H335	May cause respiratory irritation				
H411	Toxic to aquatic life with long lasting effects				
R22		Harmful if swallowed			
R36	Irritating to eyes				
R36/38		Irritating to eyes and skin			
R37/38		Irritating to respiratory system and skin			
R38		Irritating to tophatoly system and shin			
R41		Risk of serious damage to eyes			
R43					
	Toxic to aquatic of	May cause sensitisation by skin contact Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic			
R51/53	environment				
N		Dangerous for the environment			
Xi		Irrit			
Xn		Harn			
PC18					
		Ink and Toners			
PROC1		Use in closed process, no likelihood of exposure			
SU22 Profession		ses: Public domain (administration, education, entertainment,			

services, craftsmen)

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of ColDesi/Colman & Company, Inc.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

ColDesi/Colman & Company, Inc. assumes no legal responsibility for use or reliance upon this information.