

Material Safety Data Sheet (MSDS)

Adhesion Promoter for Inkjet Printing

MSDS Revision Date: December 16, 2013

Chemical Product and Company Identification

Distributed By:

Colman and Co.
5409 S West Shore Blvd
Tampa, FL 33611
800-891-1094

For Emergencies Involving a Spill, Leak, Fire, Exposure or Accident,
Contact Chemtrec (800-424-9300 within the United States or 703-527-3887
for international collect calls).

HAZARDS IDENTIFICATION

May be harmful if swallowed. Avoid breathing vapor or dust. Use with
adequate ventilation. Avoid contact with eyes, skin, and clothes. Eye
contact may cause eye irritation with discomfort, tearing or blurring of
vision. Repeated skin exposure to large quantities may result in
absorption of harmful amounts. Wash thoroughly after handling.

ADDITIONAL HEALTH EFFECTS

Since this mixture has not been tested as a whole to determine the
hazards by all routes of exposure, information is provided for each
hazardous component of the mixture to meet requirements of OSHA's
Hazard Communication Standard (29 CFR 1910.1200). The effects noted
occur from exposure to the pure component unless otherwise noted.

INFORMATION FOR COMPONENTS

Eye Contact - Can cause irritation or tearing at levels below STEL.
Skin Contact - May cause allergic skin reaction.

Inhalation - May cause respiratory disorders (sensitization). Persons with
sensitive airways may react to vapors.

Ingestion - May cause throat irritation.

Carcinogenicity Information

The following components are listed by IARC, NTP, OSHA or ACGIH as
carcinogens.

First Aid Measures

FIRST AID: SKIN: Remove contaminated clothing. Wash exposed area with soap
and water. If symptoms persist, seek medical attention

EYES: Wash eyes with plenty of water for at least 15 minutes, lifting lids
occasionally. Seek Medical Aid. INHALATION: Remove to fresh air.

INGESTION: If swallowed, contact a physician immediately. Induce vomiting

Material Safety Data Sheet (MSDS)

Adhesion Promoter for Inkjet Printing

MSDS Revision Date: December 16, 2013

after giving two glasses of water. Never give anything by mouth to an unconscious person.

COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name(s) or Synonyms</u>	<u>Material CAS Number</u>	<u>Concentration %</u>
Trade Secret	***	10 - 30%

*** Proprietary Information withheld as a trade secret. Contains no other components or impurities which will influence the classification of this product.

Fire Fighting Measures

Flash Point : >82.5 °C (>200 °F)

Method : Closed Cup

Approximate Flammable Limits in Air, % by Volume

LEL : Not Available

UEL : Not Available

Autoignition Temperature : Not Available

Product is a nonflammable water-based solution.

Hazardous combustion products (gases/vapors) produced in fire can include carbon monoxide, carbon dioxide, nitrogen oxides and smoke.

Suitable extinguishing media:

Water spray, dry extinguishing media, foam

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contaminated breathing apparatus and turn-out gear.

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations

Accidental Release Measures

Spill Clean Up:

Contain spill and soak up with absorbent material.

Material Safety Data Sheet (MSDS)

Adhesion Promoter for Inkjet Printing

MSDS Revision Date: December 16, 2013

Handling and Storage

Store in a cool, dry, well-ventilated place away from incompatible materials. Do not breathe heated vapor or dust. Do not get in eyes, on skin, or clothing. Wash thoroughly after handling. Keep container tightly closed.

Exposure Controls/ Personal Protection

Personal Protective Equipment

EYE/FACE PROTECTION

Wear safety glasses. Wear coverall chemical splash goggles and face shield when the possibility exists for eye and face contact due to splashing or spraying of the material.

RESPIRATORS

Respirators are not needed with proper ventilation. Wear an approved respirator (e.g., an organic vapor respirator or a self-breathing apparatus) whenever exposure to aerosol, mist, spray, fume or vapor exceed the exposure limit(s) of any chemical substance listed in this MSDS.

PROTECTIVE CLOTHING

If there is potential for significant dermal contact wear appropriate impervious clothing and gloves.

Applicable Exposure Limits and Exposure Data

STEL (OSHA) : 2 ppm

TWA (OSHA) : 0.75 ppm

ACTION LEVEL (OSHA) : 0.5 ppm

STEL (ACGIH) : 0.3 ppm CEILING

LD50 (rat, oral) : 100 mg/kg (supplier)

LD50 (rabbit, dermal) : 270 mg/kg (supplier)

Physical and Chemical Properties

Physical Data

Solubility in Water : Non-Miscible

Form : Liquid

Color : Clear, Transparent

Stability and Reactivity

Chemical Stability

Volatile at normal temperatures and storage conditions.

Incompatibility with Other Materials

None reasonably foreseeable.

Decomposition

None reasonably foreseeable.

Polymerization

Polymerization will not occur.

Material Safety Data Sheet (MSDS)

Adhesion Promoter for Inkjet Printing

MSDS Revision Date: December 16, 2013

Toxicological Information

There is no toxicity data available for this specific formulation. Any potential hazards are presumed to be due to exposure to the components.

Regulatory Information

According to EU Directive 88/379/EEC, this product is not classified as dangerous and therefore no hazard label is required. For other countries, no product label would be required

Other Information

Disclaimer:

The information herein is given in good faith but no warranty, expressed or implied, is made.

HMIS® Rating

Health: 2	Reactivity: 1	Flammability: 2
-----------	---------------	-----------------